

## 测温环外径与温度对照表

产品型号(Type): <b>BTC 003</b>				规格 (Dimensions): $\Phi_o20 \times \Phi_i10 \times h7\text{mm}$ , 浅绿 (Light green)			
适用温度范围(Temperature): <b>900 °C ~ 1200 °C</b>				试验条件(Condition): 空气气氛下保温 1 小时			
$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)
19.16	898	18.66	990	18.16	1039	17.66	1076
19.15	900	18.65	991	18.15	1040	17.65	1076
19.14	903	18.64	992	18.14	1041	17.64	1077
19.13	905	18.63	994	18.13	1041	17.63	1078
19.12	908	18.62	995	18.12	1042	17.62	1079
19.11	911	18.61	996	18.11	1043	17.61	1080
19.10	913	18.60	997	18.10	1044	17.60	1081
19.09	915	18.59	998	18.09	1044	17.59	1081
19.08	918	18.58	999	18.08	1045	17.58	1082
19.07	920	18.57	1000	18.07	1046	17.57	1083
19.06	922	18.56	1001	18.06	1047	17.56	1083
19.05	924	18.55	1002	18.05	1047	17.55	1084
19.04	926	18.54	1003	18.04	1048	17.54	1085
19.03	929	18.53	1004	18.03	1049	17.53	1085
19.02	931	18.52	1005	18.02	1049	17.52	1086
19.01	933	18.51	1007	18.01	1050	17.51	1087
19.00	936	18.50	1008	18.00	1051	17.50	1088
18.99	938	18.49	1009	17.99	1052	17.49	1088
18.98	940	18.48	1010	17.98	1053	17.48	1089
18.97	941	18.47	1011	17.97	1054	17.47	1090
18.96	943	18.46	1012	17.96	1055	17.46	1090
18.95	945	18.45	1013	17.95	1056	17.45	1091
18.94	947	18.44	1014	17.94	1056	17.44	1092
18.93	949	18.43	1015	17.93	1057	17.43	1092
18.92	951	18.42	1016	17.92	1058	17.42	1093
18.91	952	18.41	1017	17.91	1058	17.41	1094
18.90	954	18.40	1018	17.90	1059	17.40	1095
18.89	956	18.39	1019	17.89	1060	17.39	1095
18.88	958	18.38	1020	17.88	1060	17.38	1096
18.87	960	18.37	1021	17.87	1061	17.37	1097
18.86	962	18.36	1022	17.86	1062	17.36	1097
18.85	963	18.35	1022	17.85	1063	17.35	1098
18.84	965	18.34	1023	17.84	1063	17.34	1099
18.83	966	18.33	1024	17.83	1064	17.33	1100
18.82	968	18.32	1025	17.82	1065	17.32	1101
18.81	969	18.31	1026	17.81	1065	17.31	1102
18.80	971	18.30	1027	17.80	1066	17.30	1103
18.79	972	18.29	1028	17.79	1067	17.29	1104
18.78	974	18.28	1029	17.78	1067	17.28	1104
18.77	975	18.27	1030	17.77	1068	17.27	1105
18.76	976	18.26	1031	17.76	1069	17.26	1106
18.75	978	18.25	1032	17.75	1069	17.25	1107
18.74	979	18.24	1033	17.74	1070	17.24	1108
18.73	981	18.23	1033	17.73	1071	17.23	1108
18.72	983	18.22	1034	17.72	1071	17.22	1109
18.71	984	18.21	1035	17.71	1072	17.21	1110
18.70	985	18.20	1036	17.70	1073	17.20	1111
18.69	986	18.19	1037	17.69	1074	17.19	1112
18.68	988	18.18	1037	17.68	1074	17.18	1112
18.67	989	18.17	1038	17.67	1075	17.17	1113
						16.71	1202

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2018 - 10 - 12